Product data sheet
Characteristics

PNOTEPROC8
APC Notebook Surge Protector for AC, phone and network lines, 2 pin connection, 100-240V

Purchase

Purchase	PNOTEPROC8

Overview

Model Name	APC Notebook Surge Protector for AC, phone and network lines, 2 pin connection, 100-240V
Includes	1.8 Meter Tel cable (2),30 cm Network patch cable,Cord management straps,User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Brazil,Canada,United States

Output

Number of Outlets	1
Receptacle Style	IEC 320-C8

Input

Nominal Input Voltage	120V
Input Power	300
Input Frequency	50/60 Hz
Input Connections	IEC 320 C8
Maximum Line Current per phase	4

Surge Protection and Filtering

Surge energy rating	180
Peak Current Normal Mode	6.5
NM Surge Response Time (ns)	1
Data Line Protection	RJ-11 Modem/Fax protection (two wire single line),RJ45 10/100 Base-T Ethernet protection
Let Through Voltage Rating	< 330

Physical

Net Weight	0.1 kg
Maximum Height	27 mm
Maximum Width	32 mm
Maximum Depth	98 mm
Shipping Weight	0.2 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Shipping Height	66 mm
Shipping Width	158 mm
Shipping Depth	192 mm
Master Carton Units	12.0
Color	Silver
Units per Pallet	480.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95
Storage Elevation	0-9000 meters

Conformance

Regulatory Approvals	CSA,FCC Part 68,NOM,UL Listed
Standard Warranty	Lifetime
Equipment protection policy	Lifetime : $75000
UL 1449 TVSS Rating	700V

Sustainable Offer Status

RoHS	Compliant